BOARD WATCHER



TecScan

print inspection




Using the latest video technology, the 'Boardwatcher' inspection and monitoring system, ensures quality and integrity of many of the facets associated with corrugated products.



- Registration die cut to print
- Registration colour to colour
- Registration liner to carton
- Missing colours
- And many other features



Tel: +44 (0)1443 821552 Fax: +44 (0)1443 875569 Email: sales@tecscan.co.uk www. tecscan.co.uk





100% inspection of corrugated cardboard cartons

BASIC SPECIFICATION
High speed intelligent camera with optics (model depending on speed of machine)
High frequency lighting (strobes)
Complete set of mounting brackets
Sensor & encoder for synchronization
Camera enclosed in industrial steel housing
Alarms both Beacon & audible devices
Tecscan smartlink for connection to a monitor
17inch monitor svga

TecScan Print Inspection • 10/11 St. Davids Ind Est Pengam • Blackwood • Gwent NP12 3SW U.K.

BOARDWATCHER

SPECIFICATION

Through put 100% inspection:

at 180 boards per min [3 per second]

Board Sizes:

Unlimited width, unlimited length.

Maximum number of colours:

8 at 100% colour density. Spot and process.

Resolution: Colour to colour registration [fit] resolution <0.25mm [resolution depends on press type].

On-line re-set: Operator / Management can re-set threshold control on-line, for side lay and circumferential to suit customer.

Engineer control of outputs:

- i. Number of failed boards before the press is stopped.
- ii. Audio and visual status of the beacons.

VDU Monitor: Displays current image of the fudicial blocks and also last failed image showing which colour or colours were out of tolerance.

Isolated relay contacts for operating:-

Eject gate, coloured status beacons.

The timing of the gate eject pulse can be adjusted to suit the press.

HARDWARE

System comprises:-

CAMERA

Fire wire machine vision high resolution camera.

COMPUTER

CE approved 19" rack mounted industrial enclosure

High performance PC

Tecscan copyright software

OPERATOR INTERFACE/VDU MONITOR

Touch screen monitor

Extremely simple touch screen operators interface

Extra slave monitors can be added

ILLUMINATION

Tecscan high speed strobe technology

TRAVERSE

Heavy duty manual traverse

SYNCHRONISING SENSORS

- i. Shaft encoder supplied
- ii. Laser optic master sensor for reliable and accurate synchronisation

TRAVERSE LENGTH

To suit press width, camera enclosure carriage runs on lockable 'V' track.

OPTIONS

Other programs can be added such as:-

- i. Traverse can be motorised for remote control
- ii. System can be mounted in RITTAL enclosure
- iii. Additional cameras
- iv. Extra slave monitors can be added

INSPECTION CRITERIA

- i. Colour to colour registration
- ii. Cross track colour to colour registration
- iii. Print to board registration
- iv. Orientation
- v. Skew
- vi. Missing/feint colour

TECSCAN ELECTRONICS LIMITED

10/11 St. Davids Industrial Estate, Pengam Blackwood, Gwent. NP12 3SW

Tel: +44 (0) 1443 821552

Fax: +44 (0) 1443 875569 E;Mail: sales@tecscan.co.uk

Web Site: www.tecscan.co.uk